

Type 1 Socket - GB/T Adaptor EV Charging Model 3



Introduction

Conform to the provisions and requirements of SAE J1772,GB/T 20234.2

Using riveting pressure process with none screw , have a beautiful appearance .Hand - held design conform to the ergonomic principle, easy plug.

XLPO for cable insulation prolonging the aging resistance life - span , TPU shenth improved the bending life and wear.

Applied double color coating technology, customize color.



Feature

- GB/T and SAE Interface
- IP 55
- Connect Charging Pile (Plug Version) and Electrical Vehicle



Material

- PC+PBT Alloy
- TPE
- Copper Alloy, Silver Plated
- Silicon Ruber

Customized

- Coating Color



Product code	Speed Code	Rated current	Rated Voltage	Cable Specifications
AG-T-GS-32P	2003	32A	250V	3*6mm ² +2*0.75mm ²

Type 1 Socket - GB/T Adaptor

Current	32A
Voltage	250V
Charging Standard	SAE J1772,GB/T 20234.2

Customization Options

Cable Length	Yes
Cable Color	Yes
Plug Color	Yes
Logo Printing	Yes

Mechanical Properties

Mechanical Life	No-load Plug>10000 times
Impact of External Force	1m Drop and 2t Vehicle Run Over
Flame Retardant Grade	UL94 V-0
Operating Temperature	-30°C-+50°C
Protection	IP55 IK08
Insertion Force	<100N

Electrical Performance

Insulation Resistance	>1000MΩ (DC500V)
Pins Temperature Rise	<50K
Withstand Voltage	2500V
Contact Impedance	0.5 MΩ MAX

Certificate

Certificate	TUV,CE, RoHS
-------------	--------------